

COMMERCIAL DRIVE TABLE 4

DIVIDED COMMERCIAL DRIVEWAY					
Design Features		Curbed Roadway		Uncurbed Roadway	
		Standard	Range	Standard	Range
Intersecting Angle	A	90 degrees	75 - 105 degrees	90 degrees	75 - 105 degrees
Driveway Width	B	48 ft.	42 - 90 ft.	48 ft.	42 - 90 ft.
Entering Radius	C	25 ft.	5 - 50 ft.	25 ft.	5 - 50 ft.
Exiting Radius	D	25 ft.	5 - 50 ft.	20 ft.	5 - 50 ft.
Entrance Drive Width	K	16 ft.	16 - 30 ft.	16 ft.	16 - 30 ft.
Exit Drive Width	L	22 ft.	16 - 30 ft.	22 ft.	16 - 30 ft.
Island Width	M	10 ft.	10 - 30 ft.	10 ft.	10 - 30 ft.
Nose Offset	P	8 ft.	2 - 10 ft.	14 ft.	12 - 17 ft.
Island Length	N	35 ft.	20 - 150 ft.	35 ft.	20 - 150 ft.

The standard shall be used unless engineering judgment determines that another dimension within the range is more suitable for a particular site or a special condition is approved by the road commission.